

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/094503 A1

(51) International Patent Classification⁷: C08G 77/26,
77/18, C08K 5/07, 5/54, C08L 83/04

TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(21) International Application Number:
PCT/US2004/007873

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

(22) International Filing Date: 16 March 2004 (16.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/460,286 3 April 2003 (03.04.2003) US

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii)) for all designations

— as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii)) for the following desig-
nations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW,
BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ,
EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID,
IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ,
OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA,
ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ,
SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ,
BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE,
IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE,
SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report
— with amended claims and statement

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(71) Applicant (for all designated States except US): DOW
CORNING CORPORATION [US/US]; 2200 West
Salzburg Road, Midland, MI 48686-0994 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BERGER, Andrew
[US/US]; 2801 Dawn Road, Midland, MI 48642 (US).
LUEDER, Timothy [US/US]; 2425 North Hope Road,
Midland, MI 48642-7922 (US). SUBRAMANIAM,
Nagambal [IN/US]; 2612 Abbott Road, G7, Midland, MI
48642 (US).

(74) Agent: BROWN, Catherine, U.; Patent Department- Mail
CO1232, Dow Corning Corporation, 2200 West Salzburg
Road, Midland, MI 48686-0994 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

(54) Title: ORGANOSILOXANE COMPOSITIONS

(57) **Abstract:** A moisture curable composition capable of cure to an elastomeric body, the composition comprising (a) an organopolysiloxane having not less than two silicon-bonded hydroxyl or hydrolysable groups; (b) a silane of the general formula $G_2-Si-R^1_2$, wherein each group is reactable with the hydroxyl or hydrolysable groups in (a), and each R^1 group is an alkyl group having from 1 to 10 carbon atoms, an alkenyl group, an alkynyl group, an aryl group or a fluorinated alkyl group; (c) one or more fillers and (d) a photocatalyst. Preferably at least one R^1 group is unsaturated, but in the absence of this there is provided an additional component in the form of (e) an unsaturated compound selected from the group of an unsaturated short chain siloxane, an unsaturated cyclic siloxane, an unsaturated fatty acid, an unsaturated fatty alcohol or an unsaturated fatty acid ester. The cured product is generally used as a sealant, which avoids dirt pick-up after cure and has a protective layer on the sealant interface with air.

BEST AVAILABLE COPY

WO 2004/094503 A1